



RFID Windshield Labels





Application:

- Parking management.
- Access control.
- Tracking vehicles going in and out of parking garages.
- Car washes and stations of any sort.
- · Designed for fast and reliable vehicle identification.
- . Simply apply this convenient RFID tag onto any glass surface.
- . Thin, flexible sticker format

Key Features

- . Protected against harmful UV rays
- . Optional tamper resistant
- . Data security protected
- . Passive battery free tag

Tag Spec.:

Paper, PET layer with technique prohibit

Operating Frequency:

- HF 13.56MHz

Operating Frequency:

- HF 23.56MHz

migration - UHF 860MHz-960MHz

- 86 x 54mm - 3~10cm

Dimension: - 102mm x 76mm Read range : - 6~8 Meter, UHF Depand on the - Customized size reader and tag antenna size

0.3 mm - 0.5 mm(Release Paper layer not

Thickness: Withstand voltage: ≤5N/mm2, Waterproof Glue (Optional)

Store temperature: $-30^{\circ}\text{C} \approx +75^{\circ}\text{C}$ Antenna: AL Etching

Working temperature: $-30^{\circ}\text{C} \sim +75^{\circ}\text{C}$ Bonding: FLIP chip

Optional:

Coding: Chip Encoding

Customized Logo Printing: Double Side Offset Printing available

ID Number Printing: Serialized, Unserialized Numbers, UID number, Bar Code with Human Readable Numbers

Adhesive: Pressure-sensitive adhesive. Optional adhesive available

Data Retention 10 years

Warranty: 1 year

MOQ: 3000PCS





The information contained on this Document is considered to be confidential material proprietary to JYL-Tech, and this information shall not be disclosed, duplicated or copied for any purpose, Nor made available for any third party without the prior consent to JYL-Tech.